

FEIRO CANADA			•	
NFPA	HMIS (U.S.A.)	Rating	Protective Clothing	DOT (pictograms)
Fire Hazard	Health Hazard	0 Insignificant		Not evaluated for transport
Hoolth 1 0 Reactivity	Fire Hazard	1 Slight		Non évalué pour le transport
Health Specific hazard	Reactivity 0	2 Moderate3 High		
	Personal Protection B	4 Extreme		

Section I. Ch	Section I. Chemical Product and Company Identification				
Product Name	GM MANUAL TRANSMISSION FLUID	Code	GMMTF, 460-602-4		
		DSL	See Section 15		
Synonym	Not available.	TSCA	See Section 15		
Manufacturer	Ianufacturer PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3		Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre:		
Material Uses	Manual Transmission and Transfer Case Fluid which meets GM specification GM 9986252.		Consult local telephone directory for emergency number(s).		

Section II. Composition and Information on Ingredients						
				Ex	posure Limits (ACGII	H)
	Name	CAS#	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
and/or solvent-refined	rdrotreated and hydrocracked base oil (petroleum).	The base oil may be a mixture of the following CAS#s: 8042-47-5, 64742-46-7, 64742-52-5, 64742-54-7, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1, 178603-65-1, 178603-66-2, 445411-73-4 Mixture	-	5 mg/m³ (oil mist) Not applicable	10 mg/m³ (oil mist) Not applicable	Not established Not applicable
Manufacturer Recommendation	Not applicable					
Other Exposure Limits	Consult local, state, provincial or	territory authoriti	es for acce	eptable exposure l	imits.	

Potential Health	Prolonged or repeated contact may	cause skin iri
Effects	cause more than slight skin or eye	irritation. Wit

Section III. Hazards Identification.

rritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.

Skin Contact Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with water abrasive soap for 5 minutes or until chemical is removed. Remove contaminated clothing, shoes ar goods (e.g., watchbands, belts, etc.). If irritation persists, repeat flushing. Obtain medical advice improved completely decontaminate clothing, shoes and leather goods before reuse or discard.	nd leather
	nediately.
Inhalation Remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice	ce.

GM MANUAL TRANS	MISSION FLUID	Page Number: 2
Ingestion	NEVER give anything by mouth if victim is rapidly losing consciousness, o NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of If vomiting occurs naturally, rinse mouth and repeat administration of water	water to dilute material in stomach.
Note to Physician	Not available	

Section V. Fire-	Section V. Fire-fighting Measures			
Flammability	May be combustible at high temperature.	Flammable Limits	Not available	
Flash Points	OPEN CUP: ≥180°C (356°F) (Cleveland)	Auto-Ignition Temperature	Fire Point: 205°C (401°F)	
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur. Explosion Hazards in Presence of Various Substances Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.			
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (NOx), smoke and irritating vapours as products of incomplete combustion.			
Fire Fighting Media and Instructions	NAERG96, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.			

Section VI. Accidental Release Measures

Material Release or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section VII. Ha	andling and Storage
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid eye contact. Avoid skin contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.
Storage	Store away from incompatible and reactive materials (See section 5 and 10). Keep container tightly closed. Store in dry, cool, well-ventilated area.

Section VIII. Exposure Controls/Personal Protection

Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eyes As a minimum, safety glasses with side shields should be worn when handling this material.

Body If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

Respiratory A minimum of NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister with a dust, fume of mist filter (R, or P series) may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. A NIOSHapproved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): Neoprene, Nitrile, Polyvinyl alcohol (PVA), Fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Available in French Continued on Next Page Internet: www.petro-canada.ca/msds

GM MANUAL TRANSMISSION FLUID			Page Number: 3
Section IX. Ph	ysical and Chemical Properties		
Physical State and Appearance	Viscous liquid.	Viscosity	34.26 cSt @ 40°C, 7.7 cSt @ 100°C
Colour	Dark red.	Pour Point	-51°C (-59.8°F).
Odour	Mild petroleum oil like.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	Not available	Penetration	Not applicable.
Density	0.855 kg/L @ 15°C(59°F) 7.14 lbs/US gal @ 15°C(59°F)	Oil / Water Dist. Coeff	. Not available
Vapour Density	Not available	Ionicity (in water)	Not available
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available

Section X. Stab	ility and Reactivity		
Corrosivity	Copper corrosion, 3h, 149°C (ASTM D013	0): 1b.	
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents, reducing agents and acids.	Decomposition Products	May release COx, NOx, metallic oxides, smoke and irritating vapours when heated to decomposition.

Solubility

Insoluble in water.

Available in French

Volatility

Continued on Next Page

Non-volatile

Conditions to Avoid	decomposition.
Section XI. Toxicologic	al Information
Routes of Entry	Skin contact, eye contact, inhalation, and ingestion.
Acute Lethality	Acute toxicity information is not available for the product as a whole, therefore, data for the base oils are provided below: Acute oral toxicity (LD50): >5000 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >2500 mg/m³/4h (rat).
Chronic or Other Toxic Effec	cts
Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatitis. Short-term exposure is expected to cause only slight irritation, if any.
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation.
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs). May produce a laxative effect.
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as Group A1 or A2 carcinogens by ACGIH.
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.

Internet: www.petro-canada.ca/msds

GM MANUAL TRANSMISSION	FLUID Page Number: 4
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

Section XII. Ecological Information		
Environmental Fate Not available	Persistance/ Not available Bioaccumulation Potential	
BOD5 and COD Not available	Products of Not available Biodegradation	
Additional Remarks No additional remark.		

Section XIII. Disposal Considerations				
Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.			

Section XIV. Transport Information				
DOT Classification	Not a hazardous material for transport according to the requirements of the DOT. (United States)		Not applicable	

Section XV. Regulatory Information				
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).			
	All components of this formulation are listed on the US EPA-TSCA Inventory.			
	All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS). German Water Hazard Classification (Verwaltungsvorschrift wassergefährdende Stoffe - VwVwS) WGK=2 This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. Please contact Product Safety for more information.			
DSD/DPD (EEC)	Not classified under the Dangerous Substances or Dangerous Preparations Directives.	WHMIS (Canada) Not controlled		
ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT	TDG (Canada)		
	NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	(Pictograms)		

Section XVI. Other Information			
References Available upon request. * Marque de commerce de Petro-Canada - T	Available upon request. * Marque de commerce de Petro-Canada - Trademark		
Glossary ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemical Hazard Information and Packaging Approved Supply List COD - Chemical Oxygen Demand CPR - Controlled Products Regulations DOT - Department of Transportation (U.S.A.) DSCL - Dangerous Substances Classification and Labeling	HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NFPA - National Fire Prevention Association NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act		

Continued on Next Page Internet: www.petro-canada.ca/msds Available in French

GM MANUAL TRANSMISSION FLUID Page Number: 5 TDG - Transportation Dangerous Goods (Canada) (Europe) DSD/DPD - Dangerous Substance or Dangerous Preparations TDLo/TCLo - Lowest Published Toxic Dose/Concentration Directives (Europe) TLV-TWA - Threshold Limit Value-Time Weighted Average DSL - Domestic Substance List (Canada) TLm - Median Tolerance Limit

EEC/EU - European Economic Community/European Union TSCA - Toxic Substances Control Act EINECS - European Inventory of Existing Commercial Chemical USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia

EPCRA - Emergency Planning And Community Right-To-Know Act WHMIS - Workplace Hazardous Material Information System FDA - Food and Drug Administration

For Copy of MSDS Prepared by Product Safety - RS on 7/26/2006. Internet: www.petro-canada.ca/msds

Data entry by Product Safety - RS. **Lubricants:** Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:

1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.