



NFPA	HMIS (U.S.A.)	Rating	Protective Clothing	DOT (pictograms)
Fire Hazard	Health Hazard 1	0 Insignificant		
Health 1 0 Reactivity	Fire Hazard 1	1 Slight		
Specific hazard	Reactivity 0	2 Moderate 3 High		
	Personal Protection B	4 Extreme		

Section I. Chemical Product and Company Identification					
Product Name	me GM DEXRON-VI ATF		GMDEX6CQT, GMDEX6C4U		
		DSL	See Section 15		
Synonym	GM Mat. Spec. 9986153 ATF (FF) GM Service Fill Part#: 88861003 (1 US Quart), 88861045 (1 Gallon)	TSCA	See Section 15		
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergence	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre:		
Material Uses	Material Uses Automatic transmission fluid for use in General Motors vehicles		Consult local telephone directory for emergency number(s).		

Section II. Composition and Information on In	gredients				
	Exposure Limits (ACGIH)			IH)	
Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Mixture of severely hydrotreated and hydrocracked base oil (petroleum). Other proprietary, non-hazardous additives.	The base oil may be a mixture of the following CAS#s: 8042-47-5, 64742-46-7, 64742-52-5, 64742-54-7, 72623-84-8, 72623-85-9, 72623-87-1, 178603-65-2 178603-65-2 445411-73-4 Mixture		5 mg/m³ (oil mist) Not applicable	10 mg/m³ (oil mist) Not applicable	Not established Not applicable
Manufacturer Not applicable Recommendation					
Other Exposure Consult local, state, provincial or te Limits	erritory authorit	ies for acce	ptable exposure l	imits.	

Section III. Hazards Identification.

Potential Health Effects

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments. Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.

Section IV. First	Aid Measures		
Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.		
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.		
Inhalation	evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the ictim to rest in a well ventilated area. Seek medical attention.		
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.		
Note to Physician	Not available		
Continued on Next Pa	ge Internet: www.petro-canada.ca/msds Available in French		

GM DEXRON-VI ATF	Page Number: 2
------------------	----------------

Section V. Fire-fighting Measures					
Flammability	May be combustible at high temperature.	Flammable Limits	Not available		
Flash Points	OPEN CUP: ≥180°C (356°F) (Cleveland)	Auto-Ignition Temperature	Fire Point: ≥190°C (374°F)		
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	s Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.		
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (NOx), smoke and irritating vapours as products of incomplete combustion.				
Fire Fighting Media and Instructions	NAERG2004, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.				

Section VI. Accidental Release Measures

Material Release or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section VII	Section VII. Handling and Storage				
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.				
Storage	Store in dry, cool, well-ventilated area. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).				

Section VIII. Exposure Controls/Personal Protection

Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eyes Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

Body Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.

Respiratory Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

Hands Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

GM DEXRON-VI ATF		Page Number: 3		
Section IX. Phy	sical and Chemical Properties			
Physical State and Appearance	Viscous liquid.	Viscosity	29.8 cSt @ 40°C (104°F), 6.0 cSt @ 100°C (212°F), VI=151	
Colour	Red.	Pour Point	-54°C (-65.2°F)	
Odour	Mild petroleum oil like.	Softening Point	Not applicable.	
Odour Threshold	Not available	Dropping Point	Not applicable.	
Boiling Point	Not available	Penetration	Not applicable.	
Density	0.846 kg/L @ 15°C (59°F).	Oil / Water Dist. Coe	ff.Not available	
Vapour Density	Not available	Moderateicant5s)(s	s) Not available	
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Propertie	es Not available	

Section X. Stabi	ility and Reactivity		
Corrosivity	Copper corrosion, 3h @ 149°C: 1b		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	0 0	Decomposition Products	May release COx, NOx, smoke and irritating vapours when heated to decomposition.

Solubility

Insoluble in water.

Volatility

Non-volatile.

Section XI. Toxicological Routes of Entry	Skin contact, eye contact, inhalation and ingestion.	
Acute Lethality	Acute toxicity information is not available for the product as a whole, therefore ingredients is provided below: Acute Oral toxicity (LD50): >5000 mg/kg (rat) Acute Dermal toxicity (LD50): >2000 mg/kg (rabbit) Acute Inhalation toxicity (LC50): >2500 mg/m³/4h (rat)	, data for some of the
Chronic or Other Toxic Effe	cts	
Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatitis is expected to cause only slight irritation, if any.	Short-term exposure
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhal- quantity at ambient conditions. If heated to high temperatures or subjected which produce vapours or mists, inhalation may cause respiratory tract irritation	to mechanical actions
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomit result in chemical pneumonitis (inflammation of the lungs) and/or pu accumulation of fluid in the lungs). May produce a laxative effect.	
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.	
Immunotoxicity:	Not available	
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based up and the known hazards of the components.	oon the available data
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitizal available data and the known hazards of the components.	ation, based upon the
Mutagenic:	This product is not known to contain any components at >= 0.1% that have to mutagenicity. Therefore, based upon the available data and the known components, this product is not expected to be a mutagen.	
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have reproductive toxicity. Therefore, based upon the available data and the k components, this product is not expected to be a reproductive toxin.	
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at >= 0.1% that have teratogenicity and/or embryotoxicity. Therefore, based upon the available hazards of the components, this product is not expected to be a teratogen/em	data and the known
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities th A1 or A2 carcinogens by ACGIH.	at are listed as Group
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities th 1, 2A, or 2B carcinogens by IARC.	at are listed as Group
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantiticarcinogens by NTP.	es that are listed as
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantiticarcinogens by IRIS.	es that are listed as
Continued on Next Page	Internet: www.petro-canada.ca/msds	Available in French

GM DEXRON-VI ATF	Page Number: 4
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

Section XII. Ec	ological Information			
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available	
BOD5 and COD	Not available	Products of Biodegradation	Not available	
Additional Remarks	No additional remark.			

Section XIII. Disposal Considerations

Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional Waste Disposal authorities. Ensure that waste management processes are in compliance with government requirements and

local disposal regulations.

Section XIV. Transport Information		
DOT Classification Not a hazardous material for transport according to the requirements of the DOT. (United States)		Not applicable.

Section XV. Regulatory Information

Other Regulations

This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

Does not meet the definitions of a health or physical hazard according to the OSHA - Hazard Communication Standard. (United States)

All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

DSD/DPD (EEC) Not classified under the Dangerous WHMIS (Canada) Not controlled Substances or Dangerous Preparations **Directives**

ADR (Europe) (Pictograms)

NOT EVALUATED FOR TDG (Canada) **EUROPEAN TRANSPORT** (Pictograms) NON ÉVALUÉ POUR LE



Section XVI. Other Information

References

Available upon request.

* Marque de commerce de Petro-Canada - Trademark

Glossary

Supply List

CNS - Central Nervous System

COD5 - Chemical Oxygen Demand in 5 days

CPR - Controlled Products Regulations

ACGIH - American Conference of Governmental Industrial IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

ADR - Agreement on Dangerous goods by Road (Europe) LDLo/LCLo - Lowest Published Lethal Dose/Concentration

ASTM - American Society for Testing and Materials NAERG'96 - North American Emergency Response Guide Book (1996)

BOD5 - Biological Oxygen Demand in 5 days NFPA - National Fire Prevention Association Propane Installation Code CAN/CGA B149.2

NIOSH - National Institute for Occupational Safety & Health

CAS - Chemical Abstract Services NPRI - National Pollutant Release Inventory

CEPA - Canadian Environmental Protection Act NSNR - New Substances Notification Regulations (Canada)

CERCLA - Comprehensive Environmental Response, NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration Compensation and Liability Act

CFR - Code of Federal Regulations PEL - Permissible Exposure Limit

CHIP - Chemicals Hazard Information and Packaging Approved RCRA - Resource Conservation and Recovery Act

> RTECS - Registry of Toxic Effects of Chemical Substances SARA - Superfund Amendments and Reorganization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes)

Available in French Continued on Next Page Internet: www.petro-canada.ca/msds

GM DEXRON-VI ATF Page Number: 5 DOT - Department of Transport TDG - Transportation Dangerous Goods (Canada) DSCL - Dangerous Substances Classification and Labeling TDLo/TCLo - Lowest Published Toxic Dose/Concentration TLm - Median Tolerance Limit (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations TLV-TWA - Threshold Limit Value-Time Weighted Average TSCA - Toxic Substances Control Act Directives (Europe) DSL - Domestic Substance List USEPA - United States Environmental Protection Agency EEC/EU - European Economic Community/European Union USP - United States Pharmacopoeia EINECS - European Inventory of Existing Commercial Chemical WHMIS - Workplace Hazardous Material Information System Substances EPA - Environmental Protection Agency EPCRA - Emergency Planning and Community Right to Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazard Communication Standard HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer For Copy of MSDS Prepared by Product Safety - JDW on

Internet: www.petro-canada.ca/msds

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:

1-800-201-6285

Lubricants:

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

6/9/2005.

Data entry by Product Safety - RS.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.